



Janoki Rubber Products



Standard 45° Silicone Elbows

Uses: In high temperature Turbocharger application.

Features:

- 3/4 plies or custom ply woven Aramid (Nomex) reinforcement to meet burst pressure.
- Working Temperature -65°C to + 260°C.
- Fluorocarbon / Fluoro silicone liner used for oil and petrochemicals resistance.
- Highly Flexible.
- Excellent Ozone resistance.

Sizes

Sr. No.	Hose ID, mm	Leg length 1(mm)	Leg length 2 (mm)	Wall Thickness (mm)	No. of Plies
1	9.5	150	150	4	3
2	11	150	150	4	3
3	13	150	150	4	3
4	16	150	150	4	3
5	19	150	150	4	3
6	22	150	150	4	3
7	25	150	150	4	3
8	28	150	150	4	3
9	30	150	150	4	3
10	32	150	150	4	3
11	35	150	150	4	3
12	38	150	150	4	3
13	40	150	150	4	3
14	45	150	150	4	3
15	48	150	150	4	3
16	51	150	150	5	4
17	54	150	150	5	4
18	57	150	150	5	4
19	60	150	150	5	4
20	63	150	150	5	4
21	65	150	150	5	4
22	68	150	150	5	4
23	70	150	150	5	4
24	76	150	150	5	4
25	80	150	150	5	4
26	83	150	150	5	4
27	90	150	150	5	4
28	102	150	150	5	4
29	114	150	150	5	4
30	127	150	150	5	4
31	152	150	150	5	4